





XWOLF 300

ENGINE & DRIVE SYSTEM	Engine type	single cylinder, liquid-cooled
	Displacement(cc)	271
	Bore x Stroke(mm)	72.8×65.2
	Maximum power	16.8kW/7000rpm
	Maximum torque	25.5N·m/5500rpm
	Compression ratio	11:1
	Fuel delivery	BOSCH EFI
	Transmission	CVT, L/H/N/R
	Front differential	/
	Electric power steering(EPS)	/
VEHICLE PARAMETERS	L×W×H(mm)	1940×1095×1150
	Wheel base(mm)	1210
	Ground clearance(mm)	270
	Net weight(kg)	240
	Max. Load capacity	Front 55 lbs
		Rear 88 lbs
	Fuel tank capacity	14L
Maximum speed	88km/h	

SUSPENSION	Front suspension	Dual A-arms 167mm
	Front shock absorption	Hydraulic shock absorption
	Rear suspension	Swing Arm 163mm
	Rear shock absorption	Hydraulic shock absorption
	Rocker guard	/
BRAKING	Front brake	Disc(ø170mm)
	Rear brake	Disc(ø180mm)
WHEELS	Front wheel	24×8-12
	Rear wheel	24×10-12
	Hub	Steel Wheel
OTHERS	Meter	multi-functional digital LCD meter
	Battery	Gel battery 12Ah
	Winch	2500 lbs
	Trailer ball	●
	Front and rear racks	●
	Handlebar guard	/
	External bumper	○
	DC interface & USB	●





XWOLF 550L

ENGINE & DRIVE SYSTEM	Engine type	single cylinder, liquid-cooled	
	Displacement(cc)	499.5	
	Bore x Stroke(mm)	91×76.8	
	Maximum power	34kW/6700rpm	
	Maximum torque	53N-m/5200rpm	
	Compression ratio	11:1	
	Fuel delivery	EFI	
	Transmission	CVT, P/R/N/H/L engine parking	
	Front differential	●	
	Electric power steering(EPS)	○	
VEHICLE PARAMETERS	L×W×H(mm)	2220×1190×1320	
	Wheel base(mm)	1480	
	Ground clearance(mm)	280	
	Net weight(kg)	345	
	Max. Load capacity	Front	100 lbs
		Rear	200 lbs
	Fuel tank capacity	25L	
Maximum speed	100km/h		

SUSPENSION	Front suspension	Dual A-arms 190mm
	Front shock absorption	Hydraulic shock absorption
	Rear suspension	Dual A-arms 230mm
	Rear shock absorption	Hydraulic shock absorption
	Rocker guard	●
BRAKING	Front brake	Disc(ø210mm)
	Rear brake	Disc(ø210mm)
WHEELS	Front wheel	25×8-12
	Rear wheel	25×10-12
	Hub	Steel Wheel
OTHERS	Meter	Full LCD multi-functional digital meter with color display
	Battery	Gel battery 18Ah
	Winch	2500 lbs
	Trailer ball	●
	Front and rear racks	●
	Handlebar guard	●
	External bumper	○
	DC interface & USB	●





XWOLF 1000

ENGINE & DRIVE SYSTEM	Engine type	V-twin cylinder, liquid-cooled
	Displacement(cc)	976
	Bore x Stroke(mm)	91× 75
	Maximum power	72kW/7000rpm
	Maximum torque	98N·m/5500rpm
	Compression ratio	10.9:1
	Fuel delivery	EFI
	Transmission	2WD/4WD/4WD-LOCK, Rr Torsen Differential
	Front differential	●
	Electric power steering(EPS)	3 models
VEHICLE PARAMETERS	L×W×H(mm)	2368×1266×1482
	Wheel base(mm)	1500
	Ground clearance(mm)	305
	Net weight(kg)	459
	Max. Load capacity	Front 100 lbs
		Rear 200 lbs
	Fuel tank capacity	33L
Maximum speed	120km/h	

SUSPENSION	Front suspension	Dual A-arms 235mm
	Front shock absorption	Gas, compression/rebound adjustable
	Rear suspension	Dual A-arms 255mm
	Rear shock absorption	Gas, compression/rebound adjustable
	Rocker guard	●
BRAKING	Front brake	Disc(ø230mm)
	Rear brake	Disc(ø220mm)
WHEELS	Front wheel	27×9R14
	Rear wheel	27×11R14
	Hub	cast-aluminum
OTHERS	Meter	7in Full LED multi-functional digital meter with color display
	Battery	Gel battery 32Ah
	Winch	3500 lbs
	Trailer ball	●
	Front and rear racks	●
	Handlebar guard	●
	External bumper	○
	DC interface & USB	●